



ENVIRONMENTAL IMPACT RESEARCH PROGRAM

TECHNICAL REPORT EL-86-46

ROTARY SPREADERS

Section 8.3.1, US ARMY CORPS OF ENGINEERS WILDLIFE RESOURCES MANAGEMENT MANUAL

by

Ted B. Doerr

Environmental Laboratory

DEPARTMENT OF THE ARMY Waterways Experiment Station, Corps of Engineers PO Box 631, Vicksburg, Mississippi 39180-0631



July 1986 Final Report

Approved For Public Release; Distribution Unlimited

Prepared for DEPARTMENT OF THE ARMY
US Army Corps of Engineers
Washington, DC 20314-1000
Under EIRP Work Unit 31631

Destroy this report when no longer needed. Do not return it to the originator.

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

REPORT DOCUMENTATION PAGE							Form Approved OMB No. 0704-0188		
1a. REPORT SECURITY CLASSIFICATION				1b. RESTRICTIVE MARKINGS					
	ssified			İ					
2a. SECURITY CLASSIFICATION AUTHORITY				3. DISTRIBUTION/AVAILABILITY OF REPORT					
2b. DECLASSIFICATION/DOWNGRADING SCHEDULE				Approved for public release;					
4. PERFORMING ORGANIZATION REPORT NUMBER(S)				distribution unlimited. 5. MONITORING ORGANIZATION REPORT NUMBER(5)					
Techn	ical Repor	rt EL-86-46	·						
B .		ORGANIZATION	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION					
	USAEWES Environmental Laboratory								
6c. ADDRESS	(City, State, ar	nd ZIP Code)	<u> </u>	71 4000556 (3)					
	(0.1), 0.0.0, 0.	id zii codey		76. ADDRESS (C	7b. ADDRESS (City, State, and ZIP Code)				
PO Bo		39180-0631							
8a, NAME OF	FUNDING/SPO	ONSORING	8b. OFFICE SYMBOL	0.0006.00					
ORGANIZ		511301(III)	(If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER					
US Ar	nv Corps o	of Engineers		[
8c. ADDRESS	City, State, and	d ZIP Code)		10. SOURCE OF FUNDING NUMBERS					
				PROGRAM	PROJECT	TASK		WORK UNIT	
Washi	ngton, DC	20314-1000		ELEMENT NO.	NO.	NO.		ACCESSION NO.	
11 TITLE (Inc.	lude Security C	-1		<u> </u>	<u> </u>	1		EIRP 31631	
			2 1 22 1 2						
	/ Spreader ement Manu	s: Section 8	.3.1, US Army Co	orps of Engi	neers Wildl	ife Re	source	s	
12. PERSONAL	AUTHOR(S)	aı							
	Ted B.								
13a. TYPE OF		13b. TIME CO	OVERED	14. DATE OF REPO	14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT				
	report	FROM	то	July 1986					
	NTARY NOTAT								
Availa	ible from	National Tech	nical Informatio	on Service,	5285 Port R	oyal R	oad, S	pringfield,	
VA 22	COSATI								
FIELD	GROUP	SUB-GROUP	Applicator	Continue on reverse if necessary and identify by block number) Rotary Spreader				(number)	
		305 01.001	Equipment			ent		1	
			Spreader	Soil amendment equipment Site reclamation					
19. ABSTRACT	(Continue on	reverse if necessary	and identify by block n						
the Co and ma descri	or Engine rps Distr terials a ption, op	ers Wildlife l ict or project vailable for l eration, maint	rotary spreaders Resources Manage t biologist with habitat developm tenance, limitat	ement Manual the select ment and man tions, and a	. The repo ion and use ipulation. vailability	rt is o of typ Topics	lesigne pes of cover	ed to assist equipment red include	
or see reclam spread and as provid	d over the ation and ers are sembly of ed. Methodological decreases are sembly of the control of	e soil surface habitat impro tated, and use equipment are ods of operati	plicators used to the	monly used of Managements wildlife of the strated o	throughout it objective nabitat are and generate tenance and	the Uni es for discus	ted Stusing sed.	ates for rotary The design	
		LITY OF ABSTRACT	21. ABSTRACT SECURITY CLASSIFICATION						
■ UNCLASSIFIED/UNLIMITED				Unclassified					
22a. NAME OF	- KESPONSIBLE	INDIVIDUAL	22b. TELEPHONE (Include Area Code) 22c. OFFICE SYMBOL						
DD FORM 14	72	92.40	Redition may be used up						

PREFACE

This work was sponsored by the Office, Chief of Engineers (OCE), US Army, as part of the Environmental Impact Research Program (EIRP), Work Unit 31631, entitled Management of Corps Lands for Wildlife Resource Improvement. The Technical Monitors for the study were Dr. John Bushman and Mr. Earl Eiker, OCE, and Mr. Dave Mathis, Water Resources Support Center.

This report was prepared by Mr. Ted B. Doerr, Range Science Department, Colorado State University, Fort Collins, Colo. Mr. Doerr was employed by the Environmental Laboratory (EL), US Army Engineer Waterways Experiment Station (WES), under an Intergovernmental Personnel Act contract with Colorado State University during the period this report was prepared. Mr. Chester O. Martin, Team Leader, Wildlife Resources Team, Wetlands and Terrestrial Habitat Group (WTHG), EL, was principal investigator for the work unit. Personnel from the following companies supplied information on spreaders: Big Wheel, Inc., Paxton, Ill.; Chadwick, Inc., Sherwood, Oreg.; KMN Modern Farm Equipment, Inc., W. Memphis, Arkansas; Rambling Rotors, Inc., LaGrande, Oreg.; Simplex Manufacturing Company, Portland, Oreg.; and Wilmar-Henderson Manufacturing, Wilmar, Minn. Review and comments were provided by Mr. Martin, WES, and Mr. Larry E. Marcy, Texas A&M University.

The report was prepared under the general supervision of Dr. Hanley K. Smith, Chief, WTHG, EL; Dr. Conrad J. Kirby, Chief, Environmental Resources Division, EL; and Dr. John Harrison, Chief, EL. Dr. Roger T. Saucier, WES, was Program Manager, EIRP. The report was edited by Ms. Jessica S. Ruff of the WES Information Products Division (IPD). Drawings were prepared by Mr. John R. Harris, Scientific Illustrations Section, IPD, under the supervision of Mr. Aubrey W. Stephens, Jr.

COL Allen F. Grum, USA, was the previous Director of WES. COL Dwayne G. Lee, CE, is the present Commander and Director. Dr. Robert W. Whalin is Technical Director.

This report should be cited as follows:

Doerr, Ted B. 1986. "Rotary Spreaders: Section 8.3.1, US Army Corps of Engineers Wildlife Resources Management Manual," Technical Report EL-86-46, US Army Engineer Waterways Experiment Station, Vicksburg, Miss.

NOTE TO READER

This report is designated as Section 8.3.1 in Chapter 8 -- EQUIPMENT, Part 8.3 -- SOIL AMENDMENT EQUIPMENT, of the US ARMY CORPS OF ENGINEERS WILD-LIFE RESOURCES MANAGEMENT MANUAL. Each section of the manual is published as a separate Technical Report but is designed for use as a unit of the manual. For best retrieval, this report should be filed according to section number within Chapter 8.

ROTARY SPREADERS

Section 8.3.1, US ARMY CORPS OF ENGINEERS WILDLIFE RESOURCES MANAGEMENT MANUAL

DESCRIPTION	. 7
OPERATION	
MAINTENANCE 4 LITERATURE CITED	

Rotary spreaders are applicators used to broadcast dry fertilizer, lime, herbicides, or seed over the soil surface. They range in size from hand-held models to trailer-, truck-, and helicopter-mounted models. Hand-held spreaders are best adapted for treating small areas or sites that are inaccessible to ground equipment. Helicopter-mounted spreaders are used for treating large areas that are inaccessible or too rough for ground machinery. Both hand-held and helicopter-mounted spreaders have been used to seed and fertilize areas to improve forage quantity and quality and to reduce erosion. Trailer- and truck-mounted spreaders are generally used to apply lime and fertilizer over large areas for enhanced plant growth. Rotary spreaders are versatile application tools that are commonly used throughout the United States for reclamation and habitat improvement projects.

DESCRIPTION

Rotary spreaders have a slant-sided hopper that is loaded from the top. Hopper capacities range from less than 1 cu ft (hand-held models) to over 380 cu ft (truck-mounted spreaders) (Larson 1980; Chadwick, Inc. 1983; H. Niemeyer Sohne GMBH and Co. 1983; Wilmar-Henderson Manufacturing 1983a, 1983b). Many small square or round trailer-, truck-, and helicopter-mounted spreaders have an agitator to improve the mixing and flow of the material being spread (H. Niemeyer Sohne GMBH and Co. 1983; Rambling Rotors, Inc. 1983; Simplex Manufacturing Company 1983). The material passes through an opening in the bottom or bottom-rear of the hopper and is dispersed by a spinner or pendulum mechanism. Large rectangular truck- and trailer-mounted spreaders


have a conveyor belt that directs the material to the spinner at the bottom-rear of the hopper. The conveyor belt is powered by a hydraulic or power-take-off (PTO) system (Wilmar-Henderson Manufacturing 1983a, 1983b). The dispersing mechanisms are powered by electric motor, PTO, or hydraulic system. Hand-held models have a hand-crank and gear system that turns the spinner. Generalized spreader designs are shown in Figures 1 and 2; specifications are given in Table 1.


OPERATION

One person is required to operate a spreader, but extra personnel can reduce the time necessary to measure material and reload the hopper. Treatment areas should be premarked so that swath widths are equal and to ensure that no area is missed. Swaths should overlap 50% (which results in double coverage of the area) to ensure complete coverage. The metering of material should reflect the swath overlap. Metering should be verified for accuracy by running material through the spreader into some type of collector while the equipment travels a measured distance at the appropriate application speed. The material in the collectors should then be weighed and the weight to area ratio should be converted to pounds per acre to determine if the correct amount of material is being applied. Adjustments to the hopper opening or conveyor belt speed should then be made to correct any difference between desired and actual application rates. High lime requirements in the eastern United States usually require 2 applications, and the first application should be mixed with the soil by rototilling or disking before the second lime treatment is made.

MAINTENANCE

Rotary spreaders should be cleaned after each use to reduce contamination problems when different materials are used in the same hopper (e.g., lime and plant seed). All chains and sliding parts should be oiled. Rusted areas should be sanded and painted. Simple lubrication and hydraulic system check schedules are supplied by the manufacturer. Hoppers should not be covered when stored.





TRUCK-MOUNTED SPREADER

Figure 1. Tractor- and truck-mounted rotary spreaders (adapted from information provided by KMN Modern Farm Equipment, Inc., and Wilmar-Henderson Manufacturing)




Figure 2. Trailer-mounted rotary spreader (adapted from information provided courtesy of Wilmar-Henderson Manufacturing)

Table 1. General specifications for rotary spreaders

	Type of Rotary Spreader							
Feature	Hand-held	Trailer- mounted	Truck- mounted	Helicopter- mounted				
Hopper capacity	0.2-0.5 cu ft	35-280 cu ft	175-380 cu ft	20-80 cu ft				
Swath widths	4-28 ft	8-80 ft	24-60 ft	25-200 ft				
Application rates		100-2000 1b/ac	up to 6000 lb/ac	1-400 lb/ac				
Operation speed			20 mph	0-60 mph				

LIMITATIONS

Accurate metering and uniform distribution of material is difficult because swath overlap is not usually precise, material is often windblown during application, and material will tend to move by wind and water after application. Rotary spreader seeding rates should be double those of drill seeding because of inaccurate metering and distribution, greater seed predation, and lower seed germination. Trailer- and truck-mounted spreaders are not adapted for use on slopes greater than 18%, in rough topography, or in areas with brush or debris.

AVAILABILITY

Rotary spreaders are available from many sources, including:

Big Wheel, Inc. P. O. Box 113 Paxton, Illinois 60957

Chadwick, Inc. 11969 SW Herman Road Sherwood, Oregon 97140

Deere and Company John Deere Road Moline, Illinois 61265

KMN Modern Farm Equipment, Inc. 406 Mound City Road W. Memphis, Arkansas 72301

Rambling Rotors, Inc. Route 2, P. O. Box 2744 LaGrande, Oregon 97850

Simplex Manufacturing Company 5224 NE 42nd Avenue Portland, Oregon 97218

Wilmar-Henderson Manufacturing P. O. Box 957 Wilmar, Minnesota 56201

LITERATURE CITED

- Chadwick, Inc. 1983. C-499 fertilizer bucket specifications. Sherwood, Oreg. 2 pp.
- Larson, J. E. 1980. Revegetation equipment catalogue. USDA For. Serv. Equipment Development Center, Catalogue No. 8042 2501. 198 pp.
- H. Niemeyer Sohne GMBH and Co. 1983. Rotast fertilizer spreaders. Specification sheet. Postfach. 3 pp.
- Rambling Rotors, Inc. 1983. Specification information. LaGrande, Oreg. 1 p.
- Simplex Manufacturing Company. 1983. Model 6000 series-spreaders. Specification sheet. Portland, Oreg. 22 pp.
- Wilmar-Henderson Manufacturing. 1983a. Lime machine-320. Specification sheet. Wilmar, Minn. 2 pp.
- . 1983b. Dry spreaders. Specification sheet. Wilmar, Minn. 5 pp.